



# INSTALLATION INSTRUCTIONS

Product: Sway Bar Lanyard kit

Part Number: JKS2039

Applications: Wrangler JK, 2007-2015

517-278-1226 • tech@jksmfg.com • www.jksmfg.com  
491 W. Garfield Avenue, Coldwater, MI 49036

## Welcome

CONGRATULATIONS on purchasing the sway bar lanyards from JKS Manufacturing. We are committed to providing you with the best products available and your satisfaction is our first priority.

## Tools Required

- 5/16" Drill
- 7/16" socket and wrench

## Parts



	Description	QTY
A	Lanyard	2
B	Bolt Pack 768	
	2 - 1/4"-20 x 3/4" bolt	2
	2 - 1/4"-20 nylock nut	2
	2 - 1/4" USS washer	4

## Important

**NOT COMPATIBLE WITH** aftermarket swaybars. Install product with Original Equipment swaybar only.

**NEVER DISCONNECT** swaybar when operating vehicle on public roads.

**WHEN DISCONNECTED**, the Quicker Disconnects must be completely removed from vehicle, and the swaybar must be secured to the chassis in the horizontal position to prevent interference with tires.

## Installation

- ☐ 1. LANYARD INSTALLATION
  - Disconnect the sway bar links and rotate the sway bar until it is horizontal.
  - Attach the lanyard to the end of the sway bar and use the lanyard to locate the mounting hole position on the side of the coil bucket.
  - Make a mark and drill a 5/16" hole through the coil bucket.



- Attach the lanyards to the drilled hole using the supplied 1/4" hardware.

---

□ 2. CORRECT OPERATION OF QUICKER DISCONNECTS WITH LANYARDS

- Remove the Click Pins from the Upper and Lower Mounting Posts.
- Completely remove Quicker Disconnects from vehicle and store safely inside vehicle. **HINT: To avoid losing Click Pins, reinstall them on mounting posts while Quicker Disconnects are removed.**
- Connect the lanyards to the end of the sway bar to secure it in the in the horizontal position.

**IMPORTANT: When disconnected, the swaybar must be secured in the horizontal position to prevent interference with the tires. Failure to secure the swaybar correctly can lead to severe tire damage.**

- To reconnect, disconnect the lanyards, remove click pins from mounting posts, and the rotate swaybar down.
- Slide Quicker Disconnects back onto the mounting posts and reinstall Click Pins. **HINT: Install passenger side Quicker Disconnect first for easist reinstallation.**

If you encounter any problems with your installation and setup, please contact JKS Manufacturing for technical assistance.

JKS Technical Support	
Phone	517-278-1226
E-Mail	tech@jksmfg.com

Troubleshooting

If swaybar does not rotate freely, remove from vehicle, clean and apply rubber lubricant to chassis-mounted bushings, and reinstall.

---

©2014 JKS Manufacturing, Inc & Aftermarketing, LLC  
Revision Date 11/21//2014